

Werkstoffqualität <i>Quality of material</i>	O-Ring / Quad-Ring / Rundschnur-Ring Profildichtungen (2) Farbe <i>Rings + Gaskets Colour</i>	Vulkanisate Farbe / Kennbuchstabe <i>Vulcanizate colour/code letter (1)</i>	zu verwendendes Schmiermittel <i>lubricant to use</i>
F K M Viton	Orange <i>orange</i>	Orange / V <i>orange / V</i>	Arcanol
F K M BF750	Gold <i>golden</i>	Gold / B <i>golden / B</i>	Arcanol
F K M Vi899	Lila <i>violet</i>	Lila / Z <i>violet / Z</i>	Arcanol
F K M Viton GF-S	Weiß <i>white</i>	Weiß / G <i>white / G</i>	Arcanol
F K M Viton Tieftemp. / <i>low temp.</i>	Orange + Weiß <i>orange + white</i>	Orange + Weiß / T <i>orange + white / T</i>	Arcanol
N B R Perbunan	ohne <i>without</i>	ohne / N <i>without / N</i>	Arcanol
H N B R 70 88625	Blau + Rot <i>blue + red</i>	Blau + Rot / H <i>blue + red / H</i>	Arcanol
E P D M Ethylen-Propylen / <i>ethylene propylene diene M-class</i>	Grün <i>green</i>	Grün / E <i>green / E</i>	Elkalub GLS 867 <i>Elkalub GLS 867</i>
E P D M 70 55985 peroxid. vernetzt / <i>peroxid. crosslinked</i>	Grün + Blau <i>green + blue</i>	Grün + Blau / D <i>green + blue / D</i>	Elkalub GLS 867 <i>Elkalub GLS 867</i>
E P D M < 100 Ohm/cm	Grün + Gelb <i>green + yellow</i>	Grün + Gelb / O <i>green + yellow / O</i>	Elkalub GLS 867 <i>Elkalub GLS 867</i>
T F E / P Aflas / AF150P	Blau <i>blue</i>	Blau / A <i>blue / A</i>	Arcanol
F F K M Aflas / A75H	Silber <i>silver</i>	Silber / L <i>silver / L</i>	Arcanol
C R Neopren	Rot <i>red</i>	Rot / C <i>red / C</i>	Arcanol
F F K M Perfluoroelastomere	ohne <i>without</i>	ohne / F <i>without / F</i>	Arcanol
F F K M Kalrez 7075	Weiß + Gold <i>white + golden</i>	Weiß + Gold / K <i>white + golden / K</i>	Arcanol
Silikon <100Ohm/cm	Gelb <i>yellow</i>	Gelb / S <i>yellow / S</i>	Arcanol